



Phase three of shared use facility between Needingworth & Bluntnisham - Rockmeadow to Bluntnisham

Notes

- Footway construction to consist of 25mm AC6 surface course, 60mm AC14 binder course, 150mm compacted plantings as sub base (HSC/SD/601).
- Signs to be mounted outside useable footway where possible, mounting height 2.1m.
- Signs above footway to have min mounting height of 2.3m.
- Footway to be bounded by timber edgings to rear (both sides where offset), HB2 concrete kerbs to carriageway.

Standard details

- HSC/SD/601 - Footway construction;
- HSC/SD/501 & 502 - Kerbs/channels/edgings;
- HSC/SD/308 - Kerb offlets;

Signs/markings

- Diag 1057 - 750mm;
- Ped symbol - 980mm;
- Diag 1058 - 1m letters;
- Diag 1059 - 1m arrow;
- Diag 956 - 300mm Ø;
- Diag 956 - 40mm x-height;
- Diag 950 - 900mm;
- Diag 950.1 - 100 x-height

Date	Ref.	Revisions



Project

St Ives
Cycle Route 12

Title

Phase 3
A1123
Sheet 1 of 2

Scale	Drawn	Checked	Date
1:500	RH	RH	05/01/16

Based upon Ordnance Survey material with the permission of the controller of Her Majesty's Stationery Office © Crown Copyright. Unauthorised reproduction infringes copyright and may lead to prosecution. Cambridgeshire County Council
100023206 (2006)

Drawing Number
RH/PROJA/14696/06B